



File
LR3081

CERTIFICATE OF COMPLIANCE
(ISO TYPE 3 CERTIFICATION SYSTEM)

Issued to	i.safe MOBILE GmbH	
Address	i_Park Tauberfranken 10 97922 Lauda-Koenigshofen Germany	
Project Number	LR3081-3	
Product	Intrinsically Safe 5G Smartphone	
Model Number	IS540.2	
Electrical Ratings	Internally battery operated. Permanently installed Lithium-ion-polymer battery (4400mAh)	
Markings	Class I, Division 2, Group ABCD, T4 Class II, Division 2, Group FG, T4 Class III, Division 2, T4 Intrinsically Safe -20°C ≤ Tamb ≤ 55°C IP64	
Applicable Standards	CSA C22.2 No. 60079-0:15 CSA C22.2 No. 60079-11:14	UL 60079-0 7th ed. UL 60079-11 6th ed. UL 913 8th ed.
Factory/Manufacturing Location	i_Park Tauberfranken 10 97922 Lauda-Koenigshofen, Germany	
Conditions of Certification	See Annex A	

Statement of Compliance: The product(s)/equipment identified in this Certificate and described in the Certification Report covered under the above referenced project number have been investigated and found to be in compliance with the relevant requirements of the above referenced standard(s). As such, they are eligible to bear the QPS Certification Mark shown below, in accordance with the provisions of QPS's Service Agreement.

IMPORTANT NOTE: In order to maintain the integrity of the QPS Mark(s), certification will be revoked if:

- (1) Compliance to the above-mentioned Standard(s), or those identified in future QPS Standard Update Notice – SUN (QSD 55) is not maintained, or,
- (2) If the product/equipment is modified after certification is granted without prior written consent by QPS



Issued By: Rob Kohuch, Senior Engineer - Hazardous Locations [Ex Products]

Signature: *Rob Kohuch*

Date: November 10, 2023



The SCC and IAS Accreditation Symbols are official symbols of the respective accreditation bodies, used under license.

81 Kelfield St., Unit 8, Toronto, ON M9W 5A3 Tel: 416-241-8857; Fax: 416-241-0682

www.qps.ca





Annex A: Conditions of Certification:

1. The battery may only be charged and replaced outside of the hazardous area only.
2. The device must be protected from impacts with high impact energy, against excessive exposure to UV light and high electrostatic discharge.
3. The covers of all interfaces (USB, ISM interface) must be closed.
4. The device is intended to be carried over during use in the hazardous area.
5. The Headsets IS-HS2A.1, IS-HDHS1x.1 and the PTT Button IS-PTTB1A.1 or other accessories approved by i.safe MOBILE GmbH may be used within explosion hazardous areas only if connected to the ISM interface. The connector must be securely fastened to the ISM interface.
6. The microSD cards IS-SD164.1 and IS-SD1128.1 may be used in the corresponding slot in the hazardous area. Alternatively, the SD card port has the following intrinsic safety entity parameters:
Uo/Voc=4.35 V
Co/Ca=80 μ F
Lo/La=1 μ H
A commercially available microSD card may be used in the corresponding slot in potentially explosive atmospheres. The internal electrical capacitance and inductance are negligible, respectively correspond to the intrinsically safe connection parameters.
7. Nano-SIM cards which comply with the following intrinsic safety entity parameters, may be used in the corresponding slots in the hazardous area:
Uo/Voc=4.35 V
Co/Ca=80 μ F
Lo/La=1 μ H
A commercially available nano-SIM card may be used in the corresponding slot in potentially explosive atmospheres. The internal electrical capacitance and inductance are negligible, respectively correspond to the intrinsically safe connection parameters.